


**150-190, T90  
2310, 2510 & 2712  
Compact Tractors**

Service Manual

9-77981

Reprinted




**CASE**

	<p><i>THIS SAFETY ALERT SYMBOL INDICATES IMPORTANT SAFETY MESSAGES IN THIS MANUAL. WHEN YOU SEE THIS SYMBOL, CAREFULLY READ THE MESSAGE THAT FOLLOWS AND BE ALERT TO THE POSSIBILITY OF PERSONAL INJURY OR DEATH.</i></p>
	<p>M171B</p>

If Safety Decals on this machine use the words **Danger, Warning or Caution**, which are defined as follows:

- **DANGER:** Indicates an immediate hazardous situation which if not avoided, will result in death or serious injury. The color associated with Danger is RED.
- **WARNING:** Indicates an potentially hazardous situation which if not avoided, will result in serious injury. The color associated with Warning is ORANGE.
- **CAUTION:** Indicates an potentially hazardous situation which if not avoided, may result in minor or moderate injury. It may also be used to alert against unsafe practices. The color associated with Caution is YELLOW.

If Safety Decals on this machine are ISO two panel Pictorial, decals are defined as follows:

- The first panel indicates the nature of the hazard.
- The second panel indicates the appropriate avoidance of the hazard.
- Background color is YELLOW.
- Prohibition symbols such as   and  if used, are RED.




# WARNING

IMPROPER OPERATION OF THIS MACHINE CAN CAUSE INJURY OR DEATH. BEFORE USING THIS MACHINE, MAKE CERTAIN THAT EVERY OPERATOR:

- Is instructed in safe and proper use of the machine.
- Reads and understands the Manual(s) pertaining to the machine.
- Reads and understands ALL Safety Decals on the machine.
- Clears the area of other persons.
- Learns and practices safe use of machine controls in a safe, clear area before operating this machine on a job site.

It is your responsibility to observe pertinent laws and regulations and follow Case Corporation instructions on machine operation and maintenance.



**Service Manual  
150-190 & T90 Compact Tractors  
2310, 2510 & 2712  
Compact Tractors**

**Rac 9-77981**

**JI Case**  
A Tenneco Company





**CASE 150, 190 AND T90 COMPACT TRACTOR**

**Table of Contents**

**I-SPECIFICATIONS**

<b>Section</b>	<b>Form No.</b>
C-Specifications, Engine . . . . .	9-77761
F-Electrical . . . . .	9-77701
Wiring Diagram, 150-190 . . . . .	9-77861
Wiring Diagram, T90 . . . . .	9-77891

**II-ENGINE**

M-Assemblies Contained in the Engine Block . . . . .	9-77711
--	---------

**III-FUEL SYSTEM**

N-Carburetor . . . . .	9-77611
NN-Fuel Pumps . . . . .	9-77741

**IV-HYDRAULIC SYSTEM**

A-How It Works . . . . .	9-77901
B-Hydraulic Pump . . . . .	9-77621
D-Control Valve . . . . .	9-77631
DD-Orbital Motor . . . . .	9-77641

**V-STEERING**

O-Steering System . . . . .	9-77661
OO-Front Axles . . . . .	9-77811

**VI-TRANSMISSION**

S-Transmission . . . . .	9-77691
--------------------------	---------



# COLT 2310, 2510 AND 2712 COMPACT TRACTORS

## Table of Contents

### II-ENGINE

<b>Section</b>	<b>Form No.</b>
10-Specifications, 2310 and 2510-HH100 . . . . .	691462
10-Specifications,2712- HH120. . . . .	691462
3, 8 -Electrical . . . . .	691462
3-Wiring Diagram . . . . .	691462
2,4,5,6,7 and 9 Assemblies Contained in the Engine Block . . . . .	691462
2, Carburetor . . . . .	691462

### IV-HYDRAULIC SYSTEM

A-How It Works . . . . .	9-77901
B-Hydraulic Pump . . . . .	9-77621
D-Control Valve . . . . .	9-77631
DD-Orbital Motor . . . . .	9-77641

### V-STEERING

O-Steering System . . . . .	9-77661
OO-Front Axles . . . . .	9-77811

### VI-TRANSMISSION

S-Transmission . . . . .	9-77691
--------------------------	---------





**10**

**Series**

**General**



**SECTION**

**C**

**SPECIFICATIONS FOR**

**K 241 AND K 301**

**ENGINES**

# K241 engine

## K241 ENGINE SPECIFICATIONS

Type	Kohler, 1 Cylinder, 4 Stroke Cycle Air Cooled, "L" Head Engine
Bore	3.250 Inches
Stroke	2.880 Inches
Piston Displacement	23.9 Cubic Inches
Compression Ratio	6 to 1
Max. Comp. at Cranking Speed (Engine at Operating Temperature)	110 to 120 PSI at Sea Level
Crankcase Vacuum (Engine Running)	5 to 10 Inches Vacuum at Sea Level
Ignition	12 Volt Coil, Breaker Point

## CYLINDER BORE

Diameter of Cylinder Bore Std. A, B	3.2505-3.2545 Inches
.010 Oversize A, B + 10	3.2605-3.2615 Inches
.020 Oversize A, B + 20	3.2705-3.2715 Inches
.030 Oversize A, B + 30	3.2805-3.2815 Inches
Cylinder Bore Must Be Bored or Honed Oversize If Taper or Out of Round Exceeds	.005 Inches

## PISTON AND PISTON PIN

Diameter of Std. Piston at Bottom of Skirt	3.2470-3.2480 Inches
Diameter of Std. Piston at Top of Skirt (Measured Just Below Oil Ring)	3.2425-3.2535 Inches
Diameter of Std. Piston at Top	3.218-3.220 Inches
Piston Pin	Full Floating Type, Retained in Place With Two Retainer Rings.
Piston Pin Bore in Piston Std.	.8595-.8596 Inches
Piston Pin Diameter Std.	.8591-.8593 Inches
.005 Oversize	.8641-.8643 Inches
Piston Pin Length	2.738-2.753 Inches
Piston Pin Fit in Piston (Select Fit)	.0000-.0003 Inches
Piston Pin Fit in Connecting Rod	.0003-.0008 Inches

## PISTON RINGS

Rings Per Piston	(2 Compression-1 Oil)
1st (Top) Compression-Chrome, Taper Face, Relief Indicates Top Side	
Side Clearance	.002-.004 Inches
Width	.093-.094 Inches
2nd Compression-Chrome, Relief Indicates Bottom Side	
Side Clearance	.0015-.0035 Inches
Width	.093-.094 Inches
3rd Oil Ring	Cast W/ Expander
Side Clearance	.001-.003 Inches
Width	.1860-.1870 Inches
Ring End Gap - When Installed in Bore	.010-.020 Inches
Replacement Ring Width	
1st. Comp.	.0925-.0935 Inches
2nd. Comp.	.0865-.0875 Inches
2nd. Comp. Rail	.0235-.0245 Inches
3rd. Oil Rail	.0235-.0245 Inches
3rd Oil Ring	.134-.135 Inches

## CONNECTING RODS

Connecting Rod Length from Center of Pin Hole To Center of Bearing Journal	5.580-5.562 Inches
Piston Pin Hole Diameter in Rod	.8596-.8599 Inches
Inside Diameter of Rod Journal, Std.	1.5005-1.5010 Inches
Undersize	1.4905-1.4910 Inches
Connecting Rod to Crank Journal Clearance	.0005-.0015 Inches
Connecting Rod to Crank End Play Clearance	.007-.016 Inches

## CRANKSHAFT AND BEARINGS

Type Main Bearings	Ball Bearings
Crankshaft Rod Journal	1.4995-1.5000 Inches

Crankshaft Rod Journal Width	1.079-1.084 Inches
Crankshaft End Play	.003-.020 Inches
Measured at Bearing Plate and Shim to Proper End Play	

## CAMSHAFT

Camshaft End Play	.005-.010 Inches
Camshaft Pin Diameter	.4980-.4985 Inches
Camshaft Inside Diameter	.4995-.5015 Inches
Camshaft Pin to Camshaft Clearance	.001-.0035 Inches
Camshaft Pin to Breaker Cam Clearance	.001-.0025 Inches

## VALVE LIFTERS

Valve Lifter Outside Diameter in Block	.6232-.6237 Inches
Valve Lifter Bore in Block	.6245-.6255 Inches
Valve Lifter to Block Clearance	.0008-.0023 Inches

## VALVES

Intake Valve Tappet Clearance (Cold)	.008-.010 Inches
Exhaust Valve Tappet Clearance (Cold)	.017-.020 Inches
Angle of Valve Face - Intake and Exhaust	44 Degrees
Valve Length - Intake and Exhaust	4.572-4.582 Inches
Max. Valve Face Runout - Intake	.0015 Inches
Max. Valve Face Runout - Exhaust	.003 Inches
Valve Head Diameter - Intake	1.370-1.380 Inches
Valve Head Diameter - Exhaust	1.120-1.130 Inches
Valve Stem Diameter - Intake	.3105-.3110 Inches
Valve Stem Diameter - Exhaust	.3090-.3095 Inches
Intake Valve Stem to Guide Clearance	.001-.0025 Inches
Exhaust Valve Stem to Guide Clearance	.0025-.004 Inches

## VALVE SEATS

Seat Angle - Intake and Exhaust	45 Degrees
Max. Seat Runout - Intake and Exhaust	.002 Inches
Seat Width - Intake	.037-.045 Inches
Seat Width - Exhaust	.031-.062 Inches
Exhaust Seat Insert	Replaceable
Outside Diameter of Exhaust Insert	1.2535-1.2545 Inches
Exhaust Insert Height	.219-.221 Inches

## VALVE GUIDES

Valve Guide Length	2.125 Inches
Valve Guide Outside Diameter	.6260-.6265 Inches
Valve Guide to Block (Press Fit)	.0005-.002 Inches
Valve Guide Inside Diameter - Before Installing	.307-.308 Inches
Ream Valve Guides After Installing to	.312-.313 Inches

## VALVE SPRINGS

Spring Free Length	1.793 Inches
Spring Pressure When Comp. to 1.469 In. (Valve Closed)	27 to 31 Lbs.
Spring Pressure When Comp. to 1.165 In. (Valve Open)	54 to 62 lbs.

## GOVERNOR

Governor Stub Shaft Outside Diameter	.3735-.3740 Inches
Governor Gear Bore for Stub Shaft	.3745-.3755 Inches
Stub Shaft to Governor Gear Clearance	.0005-.002 Inches
Governor Spring Free Length With 2 Lbs. Pre-Load	2.62 Inches
Governor Spring Extended to 2.88 Inches	5.5 to 6.5 Pounds



Type ----- Kohler, 1 Cylinder, 4 Stroke Cycle,  
Air Cooled, "L" Head Engine  
Bore ----- 3.380 Inches  
Stroke ----- 3.250 Inches  
Piston Displacement ----- 29.07 Cubic Inches  
Compression Ratio ----- 6 to 1  
Max. Comp. at Cranking Speed  
(Engine at Operating Temperature) ----- 110 to 120 PSI at Sea Level  
Crankcase Vacuum(Engine Running)--- 5 to 10 Inches Vacuum at Sea Level  
Ignition ----- 12 Volt Coil, Breaker Points

### CYLINDER BORE

Diameter of Cylinder Bore Std. A, B----- 3.3745-3.3785 Inches  
.010 Oversize A, B + 10 ----- 3.3845-3.3855 Inches  
.020 Oversize A, B + 20 ----- 3.3945-3.3955 Inches  
.030 Oversize A, B + 30 ----- 3.4045-3.4055 Inches  
Cylinder Bore Must Be Bored or Honed Oversize If Taper or Out of Round  
Exceeds ----- .005 Inches

### PISTON AND PISTON PIN

Diameter of Std. Piston at Top ----- 3.356-3.360 Inches  
Diameter of Std. Piston at Top of Skirt  
(Measured Just Below Oil Ring) ----- 3.369-3.370 Inches  
Diameter of Std. Piston at Bottom of Skirt ----- 3.371-3.372 Inches  
Piston Pin ----- Full Floating Type Retained In  
Place With Two Retainer Rings.  
Piston Pin Bore In Piston, Std. ----- .8752-.8754 Inches  
Piston Pin Diameter Std. ----- .8752-.8754 Inches  
.005 Oversize ----- .8802-.8804 Inches  
Piston Pin Length ----- 2.735-2.750 Inches  
Piston Pin Fit In Piston ----- One Thumb Push Fit  
Piston Pin Fit In Connecting Rod ----- .0003-.0008 Inches

### PISTON RINGS

Rings Per Piston ----- (2 Compression-1 Oil)  
1st(Top)Compression-Chrome, Tapered Face. Relief Indicates Top Side.  
Side Clearance ----- .002-.004 Inches  
Width ----- .078 Inches  
2nd - Compression ----- Chrome, Relief Indicates Bottom Side  
Side Clearance ----- .002-.004 Inches  
Width ----- .078 Inches  
3rd - Oil Ring ----- Cast W/Expander  
Side Clearance ----- .001-.003 Inches  
Width ----- .1870 Inches  
Ring End Gap When Installed In Bore ----- .010-.020 Inches  
Replacement Ring Width  
1st Comp. ----- .077-.078 Inches  
2nd Comp. ----- .077-.078 Inches  
3rd Oil Rail ----- .0235-.0245 Inches  
3rd Oil Ring ----- .134-.135 Inches

### CONNECTING RODS

Connecting Rod Length From Center of Pin Hole  
To Center of Bearing Journal ----- 5.295-5.297 Inches  
Piston Pin Hole Diameter In Rod ----- .8757-.8760 inches  
Inside Diameter of Rod Journal, Std. ----- 1.5005-1.5010 Inches  
Undersize ----- 1.4905-1.4910 Inches  
Connecting Rod To Crank Journal Clearance ----- .0005-.0015  
Connecting Rod To Crank End Play Clearance ----- .007-.016 Inches

### CRANKSHAFT AND BEARINGS

Type Main Bearings ----- Ball Bearings  
Crankshaft Rod Journal ----- 1.4995-1.5000 Inches  
Crankshaft Rod Journal Width ----- 1.079-1.084 Inches  
Crankshaft End Play ----- .003-.020 Inches  
Measured at Bearing Plate and Shim to Proper End Play.

### CAMSHAFT

Camshaft End Play ----- .005-.010 Inches

Camshaft Pin Diameter ----- .4980-.4985 Inches  
Camshaft Inside Diameter ----- .4995-.5015 Inches  
Camshaft Pin to Camshaft Clearance ----- .001-.0035 Inches  
Camshaft Pin to Breaker Cam Clearance ----- .001-.0025 Inches

### VALVE LIFTERS

Valve Lifter Outside Diameter In Block ----- .6232-.6237 Inches  
Valve Lifter Bore In Block ----- .6245-.6255 Inches  
Valve Lifter To Block Clearance ----- .008-.0023 Inches

### VALVES

Intake Valve Tappet Clearance (Cold) ----- .008-.010 Inches  
Exhaust Valve Tappet Clearance (Cold) ----- .017-.020 Inches  
Angle of Valve Face - Intake and Exhaust ----- 44 Degrees  
Valve Length - Intake and Exhaust ----- 4.572-4.582 Inches  
Max. Valve Face Runout - Intake ----- .0015 Inches  
Max. Valve Face Runout - Exhaust ----- .003 Inches  
Valve Head Diameter - Intake ----- 1.370-1.380 Inches  
Valve Head Diameter - Exhaust ----- 1.120-1.130 Inches  
Valve Stem Diameter - Intake ----- .3105-.3110 Inches  
Valve Stem Diameter - Exhaust ----- .3090-.3095 Inches  
Intake Valve Stem to Guide Clearance ----- .001-.0025 Inches  
Exhaust Valve Stem to Guide Clearance ----- .0025-.004 Inches

### VALVE SEATS

Seat Angle - Intake and Exhaust ----- 45 Degrees  
Max. Seat Runout Intake and Exhaust ----- .002 Inches  
Seat Width - Intake ----- .037-.045 Inches  
Seat Width - Exhaust ----- .031-.062 Inches  
Exhaust Seat Insert ----- Replaceable  
Outside Diameter of Exhaust Insert ----- 1.2535-1.2545 Inches  
Exhaust Insert Height ----- .219-.221 Inches

### VALVE GUIDES

Valve Guide Length ----- 2.125 Inches  
Valve Guide Outside Diameter ----- .6260-.6265 Inches  
Valve Guide to Block (Press Fit) ----- .0005-.002 Inches  
Valve Guide Inside Diameter - Before Installing ----- .307-.308 Inches  
Ream Valve Guides After Installing to ----- .312-.313 Inches

### VALVE SPRINGS

Spring Free Length ----- 1.793 Inches  
Spring Pressure When Comp. to 1.469 In. (Valve Closed) -27 to 31 Lbs.  
Spring Pressure When Comp. to 1.165 In. (Valve Open) ---54 to 62 Lbs.



### GOVERNOR

Governor Stub Shaft Outside Diameter ----- .3735-.3740 Inches  
Governor Gear Bore for Stub Shaft ----- .3745-.3755 Inches  
Stub Shaft to Governor Gear Clearance ----- .0005-.002 Inches  
Governor Spring Free Length with 2 Lb. Pre-Load ----- 2.62 Inches  
Governor Spring Extended to 2.88 Inches ----- 5.5 to 6.5 Inches

## GENERAL TORQUE SPECIFICATION TABLE (Revised 5-64)

**USE THE FOLLOWING TORQUES WHEN SPECIAL TORQUES ARE NOT GIVEN**

**NOTE:** These values apply to fasteners as received from supplier, dry, or when lubricated with normal engine oil. They do not apply if special graphited or moly-disulphide greases or other extreme pressure lubricants are used. This applies to both UNF and UNC threads.

SAE Grade No.	5		8 *	
Bolt head identification marks as per grade Note: Manufacturing Marks Will Vary				
	Torque Foot Pounds		Torque Foot Pounds	
Bolt Size	Min.	Max.	Min.	Max.
1/4"	9	11	12	15
5/16	15	18	24	28
3/8	35	40	45	50
7/16	54	60	70	80
1/2	80	90	110	125
9/16	110	120	160	180
5/8	150	165	220	240
3/4	260	280	380	420
7/8	360	400	600	660
1"	540	600	900	1000
1-1/8	720	800	1280	1440
1-1/4	1000	1100	1800	2000
1-3/8	1460	1680	2380	2720
1-1/2	1940	2200	3160	3560

\* Thick nuts must be used with Grade 8 bolts

GENERAL ENGINE TORQUE SPECIFICATION TABLE				
Thread Size	Torque Inch Pounds		Torque Foot Pounds	
	UNC	UNF	UNC	UNF
Bolt Size				
1/4"	70	85		
5/16	150	165		
3/8			22	25
7/16			35	45
1/2			50	70

### SPECIAL ENGINE TORQUE SPECIFICATIONS

- Cylinder Head Bolts\* ----- Torque to 33 Ft. Lbs., Loosen, Retorque to 35 Ft. Lbs.
- Connecting Rod Bolt\* ----- Torque to 25 Ft. Lbs.
- Flywheel Nut ----- Torque to 100 Ft. Lbs.
- Spark Plug ----- Torque to 27 Ft. Lbs.

\*Lubricate With Grease Upon Assembly

**NOTE:** The J I Case Company reserves the right to make improvements in design or changes in specifications at any time without incurring any obligation to install them on units previously sold.

# SECTION

# F

## ELECTRICAL SYSTEM

THE CHARGING CIRCUIT



THE STARTING CIRCUIT



IGNITION SYSTEM

**Thanks for your reading.**

**Please click here to download complete manual instantly.**

**And can also choose other manuals.**

**Feel free --->write to me with any questions.**

**Our service email:**

**manuals007@hotmail.com**